

1. Identification of Substance & Company

**Product** 

Product name Basalt Products

Other names NA Product code NA

HSNO approval HSR002545

Approval descriptionConstruction Products (Toxic [6.7A]) Group Standard 2017

UN number Not allocated

Proper Shipping NameNAPackaging groupNAHazchem codeNA

**Uses**Concrete, general building, drainage and road construction materials.

**Company Details** 

Company Winstone Aggregates LTD Address 812 Great South Road

Penrose
Auckland

New Zealand Telephone Ph 09 525 9304

> Emergency Telephone Number: +64 9 525 9305 National Poison Centre: 0800 764 766

## 2. Hazard Identification

#### **Approval**

This product is an approved substance under the Hazardous Substances and New Organisms Act (HSNO, Approval HSR002545, Construction Products (Toxic [6.7A]) Group Standard 2017). The aggregate in its granular form is considered non hazardous, however there may be traces of respirable dust present which may contain crystalline silica. This fraction has been classified as hazardous according to the criteria in the Hazardous substances (Minimum Degrees of Hazard) Notice 2017.

Classes Hazard Statement

6.7A H350 - May cause cancer if inhaled (contains crystalline silica)

6.9A H372 - Causes damage to organs through prolonged or repeated exposure if inhaled.

(may cause silicosis and effects to the lungs)

SYMBOLS

## **DANGER**



## **Other Classifications**

There are no other classifications that are known to apply.

## **Precautionary Statements**

P103 - Read label before use.

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe dust.

P281 - Use personal protective equipment as required.

P308+P313 - IF exposed or concerned: Get medical advice/ attention.

Page 1 of 6 July 2019



## 3. Composition / Information on Ingredients

Component	CAS/ Identification	Conc (%)
Basalt which may include the following constituents	NA	100%
Crystalline silica	14808-60-7	Up to 60%
Non hazardous silicates and oxides	Not known	balance

This is a commercial product whose exact ratio of components may vary. Trace quantities of impurities are also likely.

#### 4. **First Aid**

## **General Information**

You should call the National Poisons Centre if you feel that you may have been harmed by this product. The number is 0800 764 766 (0800 POISON) (24 hr emergency service).

If medical advice is needed, have this SDS, product container or label at hand. If exposed or concerned: Get medical advice/ attention.

Recommended first aid

facilities

Ready access to running water is recommended. Accessible eyewash is recommended

**Exposure** 

**Swallowed** Do NOT induce vomiting. Give a glass of water to drink. Contact a doctor if

experiencing symptoms.

Eye contact If product gets in eyes, wash material from them with running water for several minutes.

If symptoms persist, seek medical advice.

Skin contact This product is non-irritating to skin. No further measures should be required.

Inhaled If coughing, dizziness or shortness of breath is experienced, remove the patient to fresh

air immediately. If patient is unconscious, place in the recovery position (on the side) for

transport and contact a doctor.

### **Advice to Doctor**

Treat symptomatically. See Section 11 for information on potential long term health effects from exposure to very fine crystalline silica dust.

## 5. Firefighting Measures

Fire and explosion hazards:

Suitable extinguishing

substances:

Unsuitable extinguishing

substances:

Unknown.

Not applicable.

Products of combustion: Product does not burn. Dust may form irritating atmosphere. Product will react

exothermically with water. Contaminated water wil be strongly alkaline. Product may

There are no specific risks for fire/explosion for this chemical. It is non-combustible.

decompose in a fire and produce toxic or corrosive fumes.

Self-contained breathing apparatus. Safety boots, non-flammable overalls, gloves, hat **Protective equipment:** 

and eye protection.

Hazchem code: NA

## 6. Accidental Release Measures

Containment

Emergency plans to manage any potential spills must be in place.

In the event of large spillage alert the fire brigade to location and give brief description of **Emergency procedures** 

hazard. Wear protective equipment to prevent respiratory exposure. Clear area of any unprotected personnel. Sweep up the solid. Avoid creating dust. If appropriate, use a

gentle water spray to wet material to minimise dust generation.

Clean-up method

Disposal

Collect and seal in properly labelled containers or drums for disposal or recycling. Sweep up and collect recoverable material into labelled containers for recycling or salvage. This material may be suitable for approved landfill. Dispose of only in accord

with all regulations.

**Precautions** Wear protective equipment to prevent the inhalation of dusts. Work up wind or increase

ventilation.



## **Basalt Products**

**Safety Data Sheet** 

## 7. Storage & Handling

Storage Handling Stable under normal use and storage conditions.

Keep exposure to dusts to a minimum, and minimise the quantities kept in work areas. Minimise dust generation and accumulation. See section 8 with regard to personal protective equipment requirements. Avoid eye contact and inhalation of dust.

## 8. Exposure Controls / Personal Protective Equipment

## **Workplace Exposure Standards**

A workplace exposure standard (WES) has not been established by WorkSafe NZ for this product. There is a general limit of 3mg/m³ for respirable particulates and 10mg/m³ for inhalable particulates when limits have not otherwise been established.

**NZ Workplace WES-TWA** Ingredient **WES-STEL Exposure Stds** Crystalline Silica (all forms)\* 0.1mg/m<sup>3</sup> (as respirable dust) no data

## **Engineering Controls**

In industrial situations, it is expected that employee exposure to hazardous substances will be controlled to a level as far below the WES as practicable by applying the hierarchy of control required by the Health and Safety at Work Act (2015) and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016. Exposure can be reduced by process modification, use of local exhaust ventilation, capturing substances at the source, or other methods. If you believe air borne concentrations of mists, dusts or vapours are high, you are advised to modify processes or increase ventilation.

### **Personal Protective Equipment**

**Eyes** 

Protective eyewear is not normally necessary when using this product. However, it

always prudent to use protective eyewear if dust is likely. Skin

Avoid repeated or prolonged skin contact. Wear overalls, rubber boots and impervious gloves. Replace frequently. Gloves should be checked for tears or holes before use. Remove protective clothing and wash exposed areas with soap and water prior to eating, drinking or smoking. Wash contaminated clothing before re-use.

Respiratory



To prevent irritation a well fitted dust mask should be used (this is not recommended when exposure is close to the WES). A fine particulate half or full face respirator with an effective seal is recommended when airborne concentrations approach the WES (section 8). If sanding, grinding, crushing or cutting material contain sand, it is possible that the silica dust WES will be exceeded hence a respirator will be required.

## **WES Additional Information**

Air monitoring to measure the overall amount of silica dust created at various positions on the worksite and the maximum level of worker exposure (given the use of dust control methods, respirators and other measures) should be carried out on a regular bases or when new work methods or equipment is introduced. Air monitoring can be carried out by occupational hygienists or other trained personnel.

## 9. Physical & Chemical Properties

**Appearance** Powder or fine granules of varying colours

Odour no odour pН no data Vapour pressure no data **Viscosity** no data **Boiling point** no data Volatile materials no data Freezing / melting point no data

Solubility insoluble in water

Specific gravity / density no data Flash point no data Danger of explosion no data **Auto-ignition temperature** no data **Upper & lower flammable limits** no data Corrosiveness non corrosive

<sup>\*</sup> WorkSafe considers its current WES-TWA of 0.1 mg/m3 for silica-crystalline (respirable dust) to be inadequate to protect workers exposed in the workplace, based on current knowledge. It is proposed that WorkSafe adopt WES-TWA for silicacrystalline of 0.05 mg/m<sup>3</sup> (respirable fraction).



## 10. Stability & Reactivity

Stability Stable

Conditions to be avoided Containers should be kept closed in order to avoid contamination. Avoid the creation of

> dust. None known

Incompatible groups Hazardous decomposition

None known

products

Hazardous reactions None known

## 11. Toxicological Information

## Summary

IF SWALLOWED: No adverse effects anticipated under normal use conditions.

IF IN EYES: Fine dust may cause irritation when in direct contact.

IF ON SKIN: No adverse effects anticipated under normal use conditions.

IF INHALED: Short term (acute) silicosis can occur with one-off exposures to extremely high levels of fine crystalline silica dust. Other short term effects include irritation, choking and difficulty breathing.

CHRONIC EFFECTS: This substance does contain traces fine respirable crystalline silica. Crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (IARC Group 1). The carcinogenicity of silica is related to long term (e.g., 10 years) inhalation of very fine particulate (e.g., crushing of rock, sand blasting or dry cutting of bricks/concrete). Carcinogenicity of silica appears linked to development of silicosis (see systematic below) followed by complications and, eventually lung cancer. In addition to silicosis there is some evidence that exposure to respirable crystalline silica may be linked to scleroderma and an increased risk of kidney disease.

## **Supporting Data**

Acute Oral Not considered acutely toxic if swallowed. Dermal Not considered acutely toxic by dermal contact.

> Inhaled The substance is not considered acutely toxic if inhaled, however there may be irritation

of the respiratory tract if dust is inhaled. Short term (acute) silicosis (see "systemic" below) can also occur with one-off exposures to extremely high levels of fine crystalline silica dust. Other short term effects include irritation, choking and difficulty breathing.

Eye The mixture is not considered to be an eye irritant. Dust may be an eye irritant

(mechanical irritation).

Skin The mixture is not considered to be a skin irritant.

Sensitisation No ingredient present at concentrations > 0.1% is considered a sensitizer. Chronic

Mutagenicity No ingredient present at concentrations > 0.1% is considered a mutagen.

Carcinogenicity The dust resulting from this product does contain crystalline silica. Crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (IARC Group 1). Crystalline Silica triggers 6.7A classification (confirmed

carcinogen). The carcinogenicity of silica is related to long term (e.g., 10 years) inhalation of very fine particulate (e.g., from sand blasting or dry cutting of quartz containing substrates). Carcinogenicity of silica appears linked to development of silicosis (see systematic below) followed by complications and, eventually lung cancer.

Reproductive / No ingredient present at concentrations > 0.1% is considered a reproductive or developmental toxicant or have any effects on or via lactation. **Developmental** Systemic

The dust of this product is considered to be a target organ toxicant, because of the presence of crystalline silica. Crystalline silica triggers 6.9A classification if it is in the form of a fine respirable dust in an occupational (chronic exposure) setting. This is due to the development of silicosis which can occur following exposure to extremely high levels of fine silica dust. Silicosis is a type of pneumoconiosis – a disease of the lung that causes inflammation, scar tissue, lesions and fibrosis in the lung (alveolar). Symptoms

include shortness of breath, cough, fever, loss of appetite and cyanosis (bluish skin). Silicosis can occur following prolonged exposure (e.g., 10 years) to relatively high levels

of fine crystalline silica dust.

Persons with existing lung conditions may be at a higher risk of further adverse health Aggravation of existing conditions effects (as above). Smokers have an increased risk of lung cancer and silicosis.

Page 4 of 6 **Basalt Products** July 2019



## 12. Ecological Data

#### Summary

This mixture is not considered harmful or ecotoxic.

**Supporting Data** 

Aquatic No evidence of aquatic toxicity for any of the ingredients present >1%.

Bioaccumulation No evidence of bioaccumulation

**Degradability** Not applicable.

**Soil** No evidence of soil toxicity.

**Terrestrial vertebrate**Not considered to be toxic towards terrestrial vertebrates **Terrestrial invertebrate**No evidence of toxicity towards terrestrial invertebrates.

**Biocidal** no data

## 13. Disposal Considerations

**Restrictions**There are no product-specific restrictions, however, local council and resource consent

conditions may apply, including requirements of trade waste consents.

**Disposal method**Disposal of this product must comply with the Hazardous Substances (Disposal) Notice

2017 and the requirements of the Resource Management Act for which approval should be sought from the Regional Authority. The substance must be treated and therefore

rendered non-hazardous before discharge to the environment.

**Contaminated packaging**Disposal of contaminated packaging must comply with the Hazardous Substances

(Disposal) Notice 2017 clause 12. Ensure that the package is rendered incapable of containing any substance and is disposed in a manner that is consistent with the requirements of the substance it contained and the material of the package. If possible

reuse or recycle packaging.

## 14. Transport Information

Land Transport Rule: Dangerous Goods 2005 - NZS 5433:2007 This mixture is not considered a dangerous good for transport on land.

UN number: NA Proper shipping name: NA Class(es) NA Packing group: NA

Precautions: NA Hazchem code: 1T (recommended)

## 15. Regulatory Information

This product is an approved substance under the Hazardous Substances and New Organisms Act (HSNO). Approval code: HSR002545: Construction Products (Toxic [6.7A]) Group Standard 2017. All ingredient appear on the NZIoC.

## Specific Controls

Key workplace requirements are:

SDS To be available within 10 minutes in workplaces storing any quantity.

Inventory An inventory of all hazardous substances must be prepared and maintained.

Packaging All hazardous substances should be appropriately packaged including substances

that have been decanted, transferred or manufactured for own use or have been

supplied

Labelling Must comply with the Hazardous Substances (Labelling) Notice 2017.

Emergency plan Required if > 1000kg is stored.

Certified handler Not required.
Tracking Not required.

Bunding and secondary containment Required if > 1000kg is stored.

Signage Required if > 10000kg is stored.

Location compliance certificate Not required. Flammable zone Not required. Fire extinguisher Not required.

Note: The above workplace requirements apply if only this particular substance is present. The complete set of controls for a location will depend on the classification and total quantities of other substances present in that location.

## **Other Legislation**

In New Zealand, the use of this product may come under the Resource Management Act and Regulations, the Health and Safety at Work Act 2015 and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016, local Council Rules and Regional Council Plans.

Page 5 of 6 Basalt Products
July 2019



## **Basalt Products**

Safety Data Sheet

## 16. Other Information

**Abbreviations** 

Approval Construction Products (Toxic [6.7A]) Group Standard 2017, Controls, EPA.

Approval Code www.epa.govt.nz

CAS Number Unique Chemical Abstracts Service Registry Number

Ecotoxic Concentration 50% – concentration in water which is fatal to 50% of a test

population (e.g. daphnia, fish species)

**EPA** Environmental Protection Authority (New Zealand)

**HAZCHEM Code** Emergency action code of numbers and letters that provide information to emergency

services, especially fire fighters

**HSNO** Hazardous Substances and New Organisms (Act and Regulations)

International Agency for Research on Cancer

**LEL** Lower Explosive Limit

**LD**<sub>50</sub> Lethal Dose 50% – dose which is fatal to 50% of a test population (usually rats).

Lethal Concentration 50% – concentration in air which is fatal to 50% of a test population

(usually rats)

MSDS (SDS)

Material Safety Data Sheet (or Safety Data Sheet)

NZIoC New Zealand Inventory of Chemicals

STEL Short Term Exposure Limit - The maximum airborne concentration of a chemical or

biological agent to which a worker may be exposed in any 15 minute period, provided the

TWA is not exceeded

TWA Time Weighted Average – generally referred to WES averaged over typical work day

(usually 8 hours)

UEL Upper Explosive Limit
UN Number United Nations Number

WES Workplace Exposure Standard - The airborne concentration of a biological or chemical

agent to which a worker may be exposed during work hours (usually 8 hours, 5 days a week). The WES relates to exposure that has been measured by personal monitoring

using procedures that gather air samples in the worker's breathing zone.

References

Data

Unless otherwise stated comes from the EPA HSNO chemical classification information

database (CCID).

Controls EPA notices, www.epa.govt.nz, Health and Safety at Work (Hazardous Substances)

Regulations 2017, www.legislation.govt.nz

WES The latest NZ Workplace Exposure Standards, published by WorkSafe NZ and available

on their web site – www.worksafe.govt.nz.

Other References: EU ECHA, ingredients SDS's, ChemIDplus, NICNAS report on crystalline silica,

Worksafe report on crystalline silica

Review

DateReason for ReviewJuly 2019NA – new SDS

### Disclaimer

This SDS was prepared by Datachem LTD and is based on our current state of knowledge, including information obtained from suppliers. The SDS is given in good faith and constitutes a guideline (not a guarantee of safety). The level of risk each substance poses is relevant to its properties (as summarised in the SDS) AND HOW THE SUBSTANCE IS USED. While guidelines are given for personal protective equipment, such precautions must be relevant to the use. The likely HSNO classifications, are based on our experience, EPA Guidelines and international classifications. A compliance record is available on request. This SDS is copyright Datachem and must not be copied, edited or used for other than intended purpose. To contact the SDS author, email info@datachem.co.nz or phone: (09) 940 30 80.

